

Premier 500

CT/VT operated energy meter



Import/export
metering



Revenue
protection



Interoperable
communication

Accurate & interoperable comms with advance event detection for LV, MV & HV metering

Premier is the family of CT/VT operated meters, which covers a wide range of power levels and offers flexible time-of-use tariff metering and communications capabilities. Premier 500 is the latest offering from this family having enhanced event detection facility and interoperable DLMS communication protocol. It is available in various accuracy classes and wiring configurations.



Application

- CT/VT-operated industrial and commercial billing purpose
 - Remote data collection for billing and consumption analysis
 - Transformer metering, boundary metering and substation monitoring

Benefits

- A wide range for catering to various utilities requirement
 - High precision metering
 - Revenue protection
 - Suitable for doing load analysis and energy audit

Features

- True four quadrant metering
 - Import/Export metering and forwarded metering option for LT/HT systems
 - Distribution transformer metering events support viz high and low voltage, under and over load
 - Time of day metering with maximum demand registration and automatic billing
 - Backlit LCD display with annunciators for various critical events
 - Scroll lock feature for continuous display of a desired parameter on display
 - High-resolution energy display mode for dial test
 - Remote meter reading over DLMS protocol through RS 232/RS 485 port
 - Advanced event detection features for voltage, current and magnetic influences
 - Two metrology LEDs for accuracy testing of different energy types
 - Meter reading in the absence of mains, using internal battery



Technical specifications

Electrical

	LT	HT
Connection type	CT-operated	CT/VT-operated
Wiring configuration	3-phase 4-wire	3-phase 3-wire, 3-phase 4-wire
Voltage range	240 V(P-N)	110 V(P-P), 63.5 V(P-N)

Applicable to both LV and HV

Current range	-/5(10) A, -/1(2) A *
Accuracy	Class 0.2s, 0.5s for HT and Class 0.5s for LT
Mains frequency	50 Hz \pm 5%
Burden	As per standards

Compliance

Standards	IS 14697, IS 15959 part 1
-----------	---------------------------

Mechanical

Dimensions(W x H x D)	179 x 231 x 70 mm(approx.)
Weight	1 \pm 0.2 Kg
Enclosure	Engineering plastic
Sealing	Break to open enclosure, Sealing provision meter cover, optical port & ETBC

Environmental

Ingress protection	IP 54
Temperature	-10 C to +55 C(operating) -25 C to +70 C(storage)
Humidity	95% non-condensing RH

Features

Tariff rate registers	Up to 8 rate registers, for two energy channels
Maximum demand	Up to 2 types, configurable in 8 registers
Load survey	Up to 90 days load profile for 8 parameters(configurable), with 30 minute integration period.
Communication	Optical port for local communication Optional RS 232 / RS 485 port on RJ-45 for remote communication. Optional RS 485 port on RJ-45 with MODBUS

* For more details, contact your nearest sales office

Australia

sales_australia@securemeters.com
www.securemeters.com/au

Dubai

sales_middleeast@securemeters.com
www.securemeters.com/me

Europe

sales_europe@securemeters.com
www.securemeters.com/eu

India, SE Asia, Africa

sales_india@securemeters.com
www.securemeters.com/in

UK

sales_uk@securemeters.com
www.securemeters.com/uk